



# HPE OfficeConnect 1405 Switch Series



## Key features

- Entry-level switching for small offices
- Plug and play; no configuration required
- Energy efficient, with EEE and idle-port power down (v2 models)
- Quality of Service (IEEE 802.1p and DSCP)
- 3-year warranty

## Product overview

The HPE OfficeConnect 1405 Switch Series consists of plug-and-play unmanaged 5- and 8-port, Layer 2 switches designed for small offices, in both Gigabit Ethernet and Fast Ethernet configurations. The 1405 Small Office switches are preconfigured for fast, easy installation, with connections using low-cost Ethernet copper cabling. They support administration-friendly features such as auto-negotiation and automatic cable type detection (MDI/MDIX), and are FCC Class B certified and approved for both business and home office locations. All models have energy-saving features such as Energy Efficient Ethernet (EEE) and idle-port power down. All models are fanless for quiet and “green” operation, and are designed for high reliability, long life, low power consumption, and low total cost of ownership. HPE OfficeConnect 1405 switches come with a 3-year warranty, which covers the unit and adapter.

## Features and benefits

### Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p)**

Allows real-time traffic classification mapped to multiple hardware queues (Gigabit Ethernet v2 models support four hardware queues per port; other models support two hardware queues per port)

- **Class of Service (CoS)**

Prioritizes traffic by honoring Differentiated Services Code Point (DSCP)

### Connectivity

- **Auto-MDIX**

Automatically adjusts for straight-through or crossover cables on all 10/100 and 10/100/1000 ports

- **Jumbo packet support (Gigabit Ethernet models only)**

Supports up to 9216-byte frame size to improve the performance of large data transfers

### Performance

- **Half-/Full-duplex auto-negotiating capability on every port**

Doubles the throughput of every port

### Ease of use

- **Flow control**

Helps ensure reliable communications during full-duplex operation

- **Comprehensive LED display with per-port indicators**

Provides an at-a-glance view of status, activity, speed, and full-duplex operation

- **Unmanaged**

Provides plug-and-play simplicity

- **Compatible**

Supports Windows® and Mac OS platforms

### Flexibility

- **Fanless design**

Enables quiet operation for deployment in open spaces

### Additional information

- **Green initiative support**

Provides support for RoHS and WEEE regulations

- **Energy savings**

5- and 8-port models utilize the Energy Efficient Ethernet (EEE) standard (IEEE 802.3az) and idle-port power down for energy savings

### Warranty and support


- **3-year warranty**

See [hpe.com/networking/warrantysummary](http://hpe.com/networking/warrantysummary) for warranty and support information included with your product purchase.

## HPE OfficeConnect 1405 Switch Series



**HPE OfficeConnect 1405 5G v3 Switch (JH407A)**



**HPE OfficeConnect 1405 8G v3 Switch (JH408A)**

### Specifications

#### I/O ports and slots

5 RJ-45 autosensing 10/100/1000 ports  
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX,  
IEEE 802.3ab

Type 1000BASE-T); Media Type: Auto-MDIX; Duplex:  
10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

8 RJ-45 autosensing 10/100/1000 ports  
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX,  
IEEE 802.3ab

Type 1000BASE-T); Media Type: Auto-MDIX; Duplex:  
10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

#### Physical characteristics

##### Dimensions

4.5(w) x 3.6(d) x 1.4(h) in (11.43 x 9.14 x 3.56 cm)

##### Weight

0.4 lb (0.18 kg)

6.1(w) x 3.6(d) x 1.4(h) in (15.49 x 9.14 x 3.56 cm)

0.5 lb (0.23 kg)

#### Memory and processor

Packet buffer size: 1 Mb

Packet buffer size: 1.5 Mb

#### Mounting

Desktop (rear port)

Desktop (rear port)

#### Performance

100 Mb Latency

< 3.0  $\mu$ s

< 3.0  $\mu$ s

1000 Mb Latency

< 2.6  $\mu$ s

< 2.6  $\mu$ s

Throughput

up to 7.4 Mpps

up to 11.8 Mpps

Routing/Switching capacity

10 Gbps

16 Gbps

MAC address table size

2048 entries

8192 entries

#### Environment

Operating temperature

32°F to 104°F (0°C to 40°C)

32°F to 104°F (0°C to 40°C)

Operating relative humidity

15% to 95%, noncondensing

15% to 95%, noncondensing

Nonoperating/Storage temperature

-40°F to 158°F (-40°C to 70°C)

-40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity

15% to 95%, noncondensing

15% to 95%, noncondensing

Acoustic

Power: 0 dB Fanless

Fanless

#### Electrical characteristics

Frequency

50/60 Hz

50/60 Hz

Voltage

100 - 240 VAC, rated

100 - 240 VAC, rated

Maximum power rating

3.0 W

4.5 W

#### Notes

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

#### Safety

UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03

UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03

#### Emissions

EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; AS/NZS CISPR 22 Class B

EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; AS/NZS CISPR 22 Class B

#### Notes

Specifications (continued)	HPE OfficeConnect 1405 5G v3 Switch (JH407A)	HPE OfficeConnect 1405 8G v3 Switch (JH408A)
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="https://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="https://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**Standards and Protocols**

(applies to all products in series)

<b>General protocols</b>	IEEE 802.1p Priority IEEE 802.3az Energy Efficient Ethernet IEEE 802.3x Flow Control
--------------------------	--

## HPE OfficeConnect 1405 Switch Series



**HPE OfficeConnect 1405-5 V2 Switch (J9791A)**



**HPE OfficeConnect 1405-8 V2 Switch (J9793A)**

Specifications	HPE OfficeConnect 1405-5 V2 Switch (J9791A)	HPE OfficeConnect 1405-8 V2 Switch (J9793A)
<b>Ports</b>	5 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full	8 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full
<b>Physical characteristics</b>		
Dimensions	4.5(w) x 3.6(d) x 1.4(h) in (11.43 x 9.15 x 3.56 cm)	6.1(w) x 3.6(d) x 1.4(h) in (15.49 x 9.14 x 3.56 cm)
Weight	0.4 lb (0.18 kg)	0.5 lb (0.23 kg)
<b>Memory and processor</b>	packet buffer size: 384 KB	packet buffer size: 768 KB
<b>Mounting</b>	Desktop (rear port)	Desktop (rear port)
<b>Performance</b>		
100 Mb Latency	< 3.2 $\mu$ s	< 2.9 $\mu$ s
Throughput	up to 0.7 million pps	up to 1.2 million pps
Routing/Switching capacity	1 Gbps	1.6 Gbps
MAC address table size	1024 entries	2048 entries
<b>Environment</b>		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	15% to 95%, noncondensing	15% to 95%, noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	15% to 95%, noncondensing	15% to 95%, noncondensing
Acoustic	Fanless	Fanless
<b>Electrical characteristics</b>		
Frequency	50/60 Hz	50/60 Hz
Voltage	100 - 240 VAC	100 - 240 VAC
Maximum power rating	1.8 W	1.9 W
	<b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03
<b>Emissions</b>	EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; AS/NZS CISPR 22 Class B	EN 55022 Class B; ICES-003 Class B; FCC Part 15, Class B; AS/NZS CISPR 22 Class B
<b>Notes</b>		

Specifications (continued)	HPE OfficeConnect 1405-5 V2 Switch (J9791A)	HPE OfficeConnect 1405-8 V2 Switch (J9793A)
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="https://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="https://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**Standards and Protocols**  
(applies to all products in series)

<b>General protocols</b>	IEEE 802.1p Priority IEEE 802.3az Energy Efficient Ethernet IEEE 802.3x Flow Control
--------------------------	--

Learn more at  
[hpe.com/networking](https://hpe.com/networking)





---

**Sign up for updates**

---



**Hewlett Packard  
Enterprise**

---

© Copyright 2011-2013, 2015, 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Windows is a U.S. registered trademark of Microsoft Corporation.

4AA3-5134ENW, December 2016 Rev. 5